

2 ELECTRICAL AND MECHANICAL SPECIFICATIONS

Electrical Specifications

Input Voltage	24V DC
Nominal Power Input	25, 18 and 12.5 Watts
Nominal Current Input	25W: 1.04A; 18W: 0.75A; 12.5W: 0.52A
Power Supply Classification	Class 2
Power Connector	Molex 874380243 (requires Molex 874390200)
Control Connector	Molex 874370543 (requires Molex 874390700)
Control Options ¹	0 - 10V, DMX512-A-RDM ² , Bluetooth Low Energy, Lutron [®] EcoSystem
CCT and Dimming Control Connections	Connector harness, 24 gauge leads

- DMX channel configuration is done via RDM or optional wireless Tunable Color iOS app. Lutron EcoSystem requires optional Digital Control Adapter.
- Remote Device Management or RDM is a protocol enhancement to DMX512-A that allows bi-directional communication between a lighting or system controller and attached RDM compliant devices over a standard DMX line.

Mechanical Specifications

Dimensions	Diameter:	1.97 inches (50 mm)
	Height:	0.67 inches (17 mm); CTM 119NR: 0.84 inches (21.44 mm)
Light Emitting Surface	9.5, 12.75 and 22 mm	
Weight	0.12 pounds (0.06kg)	
Heat Sink Attachment	Front mount, M2.5 or 4-40 Screws	
Max Case Temperature	≤90°C	

